Appendix 61

### PURCHASE ORDER

INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier :	MOLAVE TRADING, INC.			P.O. No. :	GIAE-PO-2022-06-0651		
Address :	10683 El	ON ELON ST. STA. FE SUBD., BATONG MALA	Date : JÜNE 24, 2022				
TIN:			Mode of Procurement : PB				
Gentlemer		urnish this Office the following articles so	ubject to the terms and conditions cont	ained herein:			
Place of De Date of Del		Metrology Building		Delivery Term: 1 Payment Term:	20 cd		
Stock/ Property No.	Unit	Descr	iption	Quantity Unit Cost Amoun			
1	unit	SUPPLY, DELIVERY, LABOR, INSTALLATION AND COMMISSIONING OF ONE (1) REFRIGERATED ULTRACENTRIFUGE (FLOOR TYPE) WITH DIFFERENT ROTOR			11,060,055.00	11,060,055.00	
One (1) ı	ınit THI	ERMO SCIENTIFIC SORVALL WX100	+ ULTRACENTRIFUGE CAT 750001	100			
	Te	echnical Specifications:					
		Description	Sorvall WX 100+ Ultracentrifuge	2			
-)-		Туре	Floor Model Centrifuge				
The state of		Profile (Acceleration/Braking)	10/11 (10 and coasting)				
(4		Max. Speed	100,000 rpm				
		Max. RCF	802,000 x g (T-890 rotor)				
59.		Refrigerated	Yes				
		Amperage	16/20 A				
		Control Speed Accuracy	+2 rpm				
		Heat Output	1 kW or below				
		Noise Level	51 dBA (running at set speed, ur in-house test condition) measur in front of instrument	nder ed 1m			
		Refrigerator System Type	Thermo-module cooling system (CFC/HCFC/HFC-free), Solid-sta thermoelectric refrigeration (CF free)				
		Electrical Requirements	208/240 V 50/60 Hz				
		Certifications/Compliance	CE and cCSAus				
		Capacity	6 x 250 mL				
		Phase	Single				
		Dimensions (HWD)	34.6 x 31.1 x 27.2 in. (88 x 79 x 69 cm)				
		Net Weight	859.8 lb. (390 kg)		EMAILED		
		Program Storage	1000 programs with step-runs	@:			
		Standards	CE and cCSAus	Re Oa	coient: its: ]=](~??/ Time:		
		Temperature Range	0°C to 40°C				
		Ambient Temperature Operating Range	10°C to 30°C				
		Green Features	Energy efficient, less waste				

#### **PURCHASE ORDER**

### INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier :	MOLAVE TRADING, INC.		P.Q. No. :	GIAE-PO-2022	O-2022-06-0651		
Address :	10683 ELON ELON ST. STA. FE SUBD., BATONG MALAKE, LOS BAÑOS LAGUNA		Date : JUNE 24, 2022				
TIN:			Mode of Procureme	ent : PB			
Gentlemer		urnish this Office the following articles subject to the terms and condition:	contained herein:				
			contained herein.				
Place of De Date of Del		Metrology Building		Delivery Term: 120 cd			
Stock/	Tivery.		Payment Term :	, , , , , , , , , , , , , , , , , , ,			
Property No.	Unit	Description	Quantity	Unit Cost	Amount		
		Product Overview:					
		Non-bolt down design greatly simplifies installation and five Self-locking rotor system provides confidence that the rot Intuitive full color LCD touch screen keeps operation and so the instrument, this easy-to-navigate graphical display menus.  Monitor instrument status from across the lab with Stat Lid 47cm long LED bar mounted on the front of the instrument Automatic tube balance compensation accelerates sample balancing up to 5mm  The extensive rotor portfolio for the Sorvall WX+ ultracen microtubes to 250mL bottles-providing applications flexified by Choose Fiberlite carbon fiber rotors for unequalled provides structural integrity, else speed over the rotor lifespan  Corrosion-resistant design protects against damage solutions or other salts in the laboratory  Lightweight rotors improve ergonomics for a safer risk of damage to centrifuge equipment  Repairable	or is automatically an programing simple, Lo provides quick access ght, our multi-color, put for easy visibility preparation by allow trifuge series support polity as your lab's result durability and high priminating the need to be due to moisture, che	d securely locked posted at the front to all functions and programmable ing visual sample is labware from earch focus evolves. Derformance. derate or limit the emicals, alkaline			
		Comes complete with the following accessories:					
		1 x cat 08322 Thermo Scientific T-647.5 Fixed Angle Remain Max Capacity: 6 x 100ml Max Speed: 47,500 rpm; Max RCF: 250,259 Radius: 99.3 mm, Angle: 22.5 o Rotor Package includes: Rotor cover, Rotor cover tool, Rotor cover Rotor Cover locking Nut, Rotor Stand, Vac Lubricant, Locking Nut, Extra Overspeed D Ultracentrifuge Rotor Log Book, Instruction Washer for locking Nut	O x g  O-ring,  uum Grease, ecal(80.000 rpm)				
		1 x cat 03990 PA Ultracrimp Tube, 25/pkg, 6 tub Max Speed: 47,500 rpm; Max RCF Dim: 39 Øx 107L mm; Tube Volut Fill Volume:89mL, 25x Plug and c 1 x cat 03998 Closure, Rotor Cap 1 x cat 03940 Tube Rack 1 x cat 03920 Ultracrimp Sealing Tool	7: 250,259 x g ne: 90.0ml	,			
		1 x cat 54285Thermo Scientific AH-629 (17m Max Capacity: 6 x 17mL Max Speed: 29,000 rpm; Max RCF Radius: 166.9 mm Angle: 90 ° Rotor Package includes: Rotor Stand, Vacuum grease, Lubi 17mL buckets (qty:6), Bucket o-r Ultracentrifuge rotor log book	ricant, Extra Overs	speed decal (29.00)	ກາ		

Appendix 61

# PURCHASE ORDER INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier :	MOLA	VE TRADING, INC.	P.O. No. : GIAE-PO-2022-06-0651			
Address :	10683 ELON ELON ST. STA. FE SUBD., BATONG MALAKE, LOS BAÑOS LAGUNA		Date :	JUNE 24, 2022		
TIN:			Mode of Procurement : PB			
Gentleme		furnish this Office the following articles subject to the American		ent. FD		
0		furnish this Office the following articles subject to the terms and conditions con	tained herein:			
Place of De Date of Del		Metrology Building	Delivery Term: 120 cd			
Stock/ Property						
No.	Oilit	Description	Quantity	Unit Cost	Amount	
		1 x cat 06750 PET thin-walled tube, 50 /pk Max speed: 29,000 rpm Ma Dimension: 16Ø x 102L mm Tube Volume: 17.0 ml; Volum 1 x cat 03126 PA thin-walled tube, 50/pk, 6 Max Speed: 29,000 rpm Ma Dimension: 16Ø x 102L mm Tube Volume: 17.0 mL; Volum 1 x cat 75000414 PA- re-seal conetop tube Max Speed: 29,000 rpm, Max Tube Volume: 15mL; Volum 1 x cat 75000452 Closure, 16mm noryl crov 1 x cat 75000451 Closure 10/pk Stainless st 1 x cat 75000478 Tool, wrench  1 x cat 11672 Thermo Scientific TV-1665 Max Capacity: 16 x 6 mL Max Speed: 65,000 rpm; Max Radius: 87.8 mm, Angle: 0 o Rotor Package includes: Rotor Stand, Lubricant, Extra Instruction manual, Ultracen 2 x cat 03945 PA ultracrimp tube, 50/pk, 16 Max Speed: 65,000rpm, Max Tube Volume: 6.0mL, Volume Dimension 13Ø x 66L mm, Cl ultracrimp plugs and caps inc 1 x cat 03921 Accessory, 6mL ultracrimp tub 1 x cat 03991 Accessory Rotor Cap 1 x cat 12770 Tool Kit for ultracrimp sealing Torque wrench, socket cap w	x RCF: 155,8 ; ne Fill: 17.9r 6 tubes/roto ix RCF: 155,8 ume Fill: 16. e, 50/pk, 6 to ix RCF: 155,8 e Fill: 15.0 re vn teel plug  Vertical Ro ix RCF: 414,3 a overspeed trifuge rotor tubes/rotor RCF: 414,35 e Fill: 5.7mL osure 50/pk cluded be rack	and	rpm)	

Appendix 61

## PURCHASE ORDER INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier :	MOLAV	E TRADING, INC.	P.O. No. : GIAE-PO-		-2022-06-0651	
Address ;	10683 EI	ON ELON ST. STA. FE SUBD., BATONG MALAKE, LOS BAÑOS LAGUNA	Date :	JUNE 24, 2022		
TIN:			Mode of Procurement : PB			
Gentlemer		urnish this Office the following articles subject to the terms and conditions cont	ained herein:			
Place of De Date of Del			Delivery Term: 120 cd Payment Term:			
Stock/ Property No.	Unit	Description	Quantity	Unit Cost	Amount	
		1 x cat 75003031 Thermo Scientific SureSpin 632 (17ml) Capacity: 6 x 17 Ml Max Speed: 32,000 rpm Max RCF: 191,759 x g Tube Dimension: 16 Ø x 102mm Package includes: Rotor Stand, Vaccum Overspeed decal (32,000 rpm), 17ml b Bucket o-ring (qty.6), Instruction mani 1 x cat 06750-AV PET- thin -walled tube Tube Vol: 17mL Vol 1 50/pk, 6 tubes/rotor, Max Speed: 32,000 rpm, Max RCF: 191 Dimension: 16Ø x 102 L mm  1 x cat 03126 PA thin-walled Tube Vol: 17 mL, Vol. Fill: 16.0 M 50/pk, 6 tubes/rotor Max Speed: 32,000 rpm, max RCF: 191, Dimension: 16Ø x 102 L mm  1 x cat 79290 Thermo Scientific StepSaver 65V13 (6ML) Y Capacity: 8 x 6mL Max Speed: 65,000 rpm Max RCF: 393,120 x g Tube Dimension: 13Ø x 66 mm L  1 x cat 79273 PA ultracrimp tube, Tube Vol: 6.0 mL, Vol Fill: 5 50/pk, 8 tubes/rotor Max Speed: 65,000 rpm Max RCF: 393,120 x g Tube Dimension: 13Ø x 66 mm L  1 x cat 79297 6mL utracrimp cartridge set closure 1 x cat 03921 Tube Rack 1 x cat 03921 Tube Rack 1 x cat 03920 Ultracrimp sealing tool  1 x Socomec ITYS 2 UPS Model ITY3-TW100B, 10 KVA Capacit Compact Tower UPS Sytem 1 x Stavol 10KVA AVR  WARRANTY: Three (3) years from date INSTALLATIONS/TRAINING: To be done on site by our	of Grease, Lubrica uckets (qty.6), bu ual, Ultracentrifu, Fill: 17.0 mL, 759 x g  Vertical Rotor, T	nt, Extra acket rack, ge rotor log book		

22. 623TF

Appendix 61

### PURCHASE ORDER INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

	INDUSTRIAL TECHNOLOGY DEVELOPM	MENT INSTITUTE				
Supplier : Address :	MOLAVE TRADING, INC.  10683 ELON ELON ST. STA. FE SUBD., BATONG MALAKE, LOS BAÑOS LAGUNA	P.O. No. :	GIAE-PO-2022-06-0651			
TIN:	AGUNA	Date : Mode of Procurement :	JUNE 24, 2	022		
Gentlemen	n: Please furnish this Office the following articles subject to the terms and conditions co		гв			
		Delivery Term: 120 cd Payment Term:				
END USER:	BERNARD JUDE M. GUTIERREZ	Less: VAT EWT	493,752.46 98,750.49	592,502.95 <b>10,467,552.0</b> 5		
	of failure to make the full delivery within the time specified above, a penalty of one-te item/s. forme:	nth (1/10) of one percent fo Very truly yours,	or every day of delay shall	be imposed on the		
	Signature over Printed Name of Supplier	ANNABELLE V. BRIONES, PhD Signature over Printed Name of Authorized Official				
	Signature over Printed Name of Supplier  Date	Signature over	Director  Designation	еа Отпстат		
Fund Cluster:  Project 1. Isolation and Purification of Philippine Common Viruses with Medical Importance and Pandemic  Potential for Antigen-Antibody Studies		ORS/BURS No. : TFC	·20220614119			
Funds Availa	PATRICIA ASHLEY M. MENDOZA  Signature over Printed Name of Chief Account int/Head of Accounting Division/Unit	Amount:				

07/04/22

Jo 4/29/20