

13. 08.23

Appendix 61

# Purchase Order

INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Supplier :	<b>GRIMIT LABORATORY FURNITURES AND EQUIPMENT CORP.</b>	P.O. No. :	<b>GIAE-PO-2023-04-0388 (CED)</b>
Address :	NO. 04 EAST SERVICES ROAD, APOVAL, WESTERN BICUTAN, TAGUIG CITY	Date :	April 28, 2023
TIN :		Mode of Procurement :	PB

Gentlemen:  
Please furnish this Office the following articles subject to the terms and conditions contained herein:

Place of Delivery :	CHEMICAL AND ENERGY DIVISION	Delivery Term :	30-60 CD
Date of Delivery :		Payment Term :	

Stock/Property No.	Unit	Particulars	Quantity	Unit Cost	Amount
1	unit	<p><i>Supply, Delivery, Installation &amp; Commissioning:</i></p> <p><b>Laboratory Side Table (Hot Room)</b></p> <p>Dimension: 1800 mm L x 650 mm W x 900 mm H</p> <p>Worktop: Durcon Solid phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact wear resistant, Easy to clean suitable for contact with food. With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge. Frame and Support: 2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot.</p> <p>Accessories: a. 2 units 2 gang Electrical outlet universal 220VAC/15amp splash mounted at 100-130mmH Splash board similar to worktop. b. 2 units Laboratory Chairs – CH04-1 A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	58,900.00	58,900.00
2	Unit	<p><b>Laboratory Side Table U-Shaped (Material Testing/Characteristic Room)</b></p> <p>Dimension: 4000mm x 4000 x 7000 mm L x 650 mm W x 900 mm H</p> <p>Worktop: Durcon Solid phenolic resin electron beam cured and double sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, Easy to clean suitable for contact with food. With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge.</p> <p>Cabinets/Drawers: Steel cold rolled sheets epoxy powder coated 40-60 µ in 200°C, 10 steps anti – rust process, chemical, corrosion and chip resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinges, adjustable shelving, recessed/ integrated handles for safety and heavy - duty caster wheel. Customize in color. At 4000mm L side: -2 units mobile cabinet single swing door -1 unit mobile cabinet double swing door -1 unit mobile cabinet lateral 4 pull out drawers At 4000mm L: -2 units mobile cabinet double swing door At 7000mm L: -3 units mobile cabinet single swing door -1 unit mobile cabinet double swing door -1 unit mobile cabinet lateral 4 pullout drawers</p> <p>Frame and Support: 2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot.</p> <p>Accessories: a. 7 units 2 gang Electrical outlet universal 220VAC/15amp splash mounted at 100-130mmH Splash board similar to worktop. b. 2 units Laboratory High Chairs – CH04-1 A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	522,900.00	522,900.00

**EMAILED**

Recipient: \_\_\_\_\_  
Date: 06-08-23 Time: \_\_\_\_\_

PO. EXT

<b>Purchase Order</b> <small>INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE</small>						Appendix 61
<b>Supplier :</b>	<b>GRIMIT LABORATORY FURNITURES AND EQUIPMENT CORP.</b>			<b>P.O. No. :</b>	<b>GIAE-PO-2023-04-0388 (CED)</b>	
<b>Address :</b>	NO. 04 EAST SERVICES ROAD, APOVAL, WESTERN BICUTAN, TAGUIG CITY			<b>Date :</b>	April 28, 2023	
<b>TIN :</b>				<b>Mode of Procurement :</b>	PB	
<b>Gentlemen:</b>	Please furnish this Office the following articles subject to the terms and conditions contained herein:					
<b>Place of Delivery :</b>	CHEMICAL AND ENERGY DIVISION			<b>Delivery Term :</b>	30-60 CD	
<b>Date of Delivery :</b>				<b>Payment Term :</b>		
Stock/ Property No.	Unit	Particulars	Quantity	Unit Cost	Amount	
3	unit	<b>Assembly Movable Table (Material Testing/Characteristic Room)</b> Dimension: 2000mmL x 750mmW x 900mmH Worktop: Durcon Solid phenolic resin electron beam cured and double sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, Easy to clean suitable for contact with food. With certification on Greenguard, SEFA 3, ISO Certification 9001 & 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge. Drawer: -1 unit mobile cabinet lateral 2 pull out drawers Frame and Support: 2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot. Accessories: a. 2 units Laboratory High Chairs – CH04-1 A PU (Polyurethane) PU seat and back + 6mm	1	69,500.00	69,500.00	
4	unit	thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.  <b>Laboratory Side Table L- Shaped with Sink and Rack (Material Sample and Preparation Room)</b>  Dimension: 6500mmx4000mmLx650mmWx900mmH Durcon Solid phenolic resin electron beam cured and double sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, Easy to clean suitable for contact with food. With certification on Greenguard, SEFA 3, ISO Certification 9001 & 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge  Cabinets/Drawers: Steel cold rolled sheets epoxy powder coated 40-60 µ in 200°C, 10 steps anti – rust process, chemical, corrosion and chip resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinges, adjustable shelving, recessed/ integrated handles for safety and heavy - duty caster wheel. Customize In color. At 6500mmL side: -3 units mobile cabinet single swing door -1 unit mobile cabinet double swing door -1 unit mobile cabinet lateral 4 pullout drawers At 4000mmL: -2 units mobile cabinet double swing door -1 unit sink base cabinet Laboratory Sink (for side table) Dimension 480mmx380mmWx285mmH/SS316 gauge 1mm industrial grade, seamless with hairline finished.  Laboratory faucet: Connection: G3/8, G1/2, G3/4, standard UNISO 228/1 Olive-shaped nozzle: DIN 12898 Normal regulation headwork or with ceramic closure. Max. working pressure 10 bar. Optional: Chemical nickel treatment Technical features: Operating temperature: 30°C to 150°C Chemical resistance: Extremely rare alternations. Salt spray test: No alternations. Kesternich test: No variation (DIN 50018). Frame and Support: 2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot.  Accessories: a. 5 units 2 gang Electrical outlet universal220VAC/15amp splash mounted at 100-130mmH Splash board similar to worktop. b. 1 Unit SS316 sink bowl seamless and hairline finish complete with traps and piping. c. 1 Unit laboratory grade swivel gooseneck faucet with serrated nozzle complete fittings. d. 1 Unit solid phenolic pegboard with 36 peg sticks PP. Pegboard- 710x710, 20mm Solid Phenolic Board chemical resistant with 36 pcs. Peg sticks. Peg stick- 120mm Polypropylene. e. Steel rack double deck with SS304 rail guide f. 2 units Laboratory High Chairs- CH04-1A PU(Polyurethane) PU seat and back +6mm thickness metal chrome plate with simple, mechanism +200mm gas lift+, dia450 stainless steel footing + dia640 chrome base + castors.	1	450,600.00	450,600.00	

No. of JF

**Purchase Order**  
INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE

Appendix 61

Supplier:	<b>GRIMIT LABORATORY FURNITURES AND EQUIPMENT CORP.</b>	P.O. No.:	<b>GIAE-PO-2023-04-0388 (CED)</b>
Address:	NO. 04 EAST SERVICES ROAD, APOVAI, WESTERN BICUTAN, TAGUIG CITY	Date:	April 28, 2023
TIN:		Mode of Procurement:	PB

Gentlemen:  
Please furnish this Office the following articles subject to the terms and conditions contained herein:

Place of Delivery:	CHEMICAL AND ENERGY DIVISION	Delivery Term:	30-60 CD
Date of Delivery:		Payment Term:	


Stock/ Property No.	Unit	Particulars	Quantity	Unit Cost	Amount
5	unit	<p><b>Center Table with End Sink and Reagent Rack (Material Sample and Preparation Room)</b></p> <p>Dimension: 3650mmLx1200mmWx900mmH</p> <p><b>Worktop:</b> Durcon Solid phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, easy to clean suitable for contact with food. With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge.</p> <p><b>Cabinets/Drawers:</b> Steel cold rolled sheets epoxy powder coated 40-60 μ in 200°C, 10 steps anti-rust process, chemical, corrosion and chips resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinges, adjustable shelving, recessed/ integrated for safety and heavy duty caster wheel.</p> <p><b>Customize in color:</b> -2 units mobile cabinet single swing door -2 units mobile cabinet double swing door -2 units lateral cabinet with 2 pull out drawers Laboratory sink(for center table): Dimension 600mmx380mmWx285mmHSS316 gauge 1mm industrial grade, seamless with hairline finished. Laboratory Faucet: Connection: G3/8, G1/2, G3/4, standard UNI ISO 228/1. Olive - shaped nozzle: DIN 12898. Normal regulation headwork or with ceramic closure. Max. working pressure 10 bar Optional: Chemical nickel treatment. Technical features: Operating temperature: 30°C to 150°C Chemical resistance: Extremely rare alternations . Salt spray test : No alternations. Kesternich test: No variation (DIN 50018). Frame and support: 2x2 Steel Tubular 2.0mm thick epoxy powder coated frame with heavy duty levelling foot. Frame and support: 2x2 Steel Tubular 2.0mm thick epoxy powder coated frame with heavy duty levelling foot.</p> <p><b>Accessories:</b> a. 6- units 2 gang Electrical outlet universal 220VAC/15amp splash mounted. b. 1unit SS316 sink bowl seamless and hairline finish compete with traps and piping. c. 1 Unit laboratory grade swivel gooseneck faucet with serrated nozzle and complete fittings. d. 1 Unit Solid Phenolic peg board with 36 peg sticks PP-Pegboard - 710x710, 20mm Solid Phenolic Board chemical resistant with 36 pcs. Peg sticks. Pegstick - 1200 Polypropylene e. Reagent rack steel powder coated rack 2 deck with SS304 rail guide. f. 2 units Laboratory High Chairs- CH04-1A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism +200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	314,800.00	314,800.00
6	unit	<p><b>Center Assembly Table (Fuel Cell Assembly and Testing Room)</b></p> <p>Dimension: 4400mmLx2200mmWx900mmH</p> <p><b>Worktop:</b> Durcon Solid Phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, Easy to clean suitable for contact food. With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties. Thickness and Color: 20 mm, Black, beveled edge.</p> <p><b>Cabinets/Drawers:</b> Steel cold rolled cold epoxy powder coated 40-60 μ in 200°C, 10 steps anti-rust process, chemical, corrosion and chip resistant with drawers in full extension heavy rail guides, swing door, soft close buffer regressing hinges, adjustable shelving recessed/ integrated handles for safety and heavy duty caster wheel. Customized in color</p> <p><b>At 4000mmL side.</b> -4 units mobile cabinet double swing door -2 units lateral cabinet with 4 pull out Frame and Support: 2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot</p> <p><b>Accessories:</b> a. 4-units 2 gang Electrical outlet universal220VAC/15amp splash mounted. b. Reagent rack steel powder coated rack 2 deck with ss304 rail guide. c. 2 units Laboratory Chairs CH04- 1A PU(Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple mechanism +200mm gas lift +dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	400,500.00	400,500.00

203. 432TF

Purchase Order						Appendix 61
INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE						
Supplier:	GRIMIT LABORATORY FURNITURES AND EQUIPMENT CORP.			P.O. No.:	GIAE-PO-2023-04-0388 (CED)	
Address:	NO. 04 EAST SERVICES ROAD, APOVAI, WESTERN BICUTAN, TAGUIG CITY			Date:	April 28, 2023	
TIN:				Mode of Procurement:	PB	
Gentlemen:	Please furnish this Office the following articles subject to the terms and conditions contained herein:					
Place of Delivery:	CHEMICAL AND ENERGY DIVISION			Delivery Term:	30-60 CD	
Date of Delivery:				Payment Term:		
Stock/ Property No.	Unit	Particulars	Quantity	Unit Cost	Amount	
7	unit	<p><b>Laboratory Side Table with Sink (Fuel Cell Assembly and Testing Room)</b></p> <p>Dimension: 1800mmLx650mmWx900mmH  <b>Worktop:</b>                      Durcon Solid phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact/wear resistant, Easy to clean suitable for contact with food.                      With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF. With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties.                      Thickness and Color: 20 mm, Black, beveled edge.  <b>Cabinets/Drawers:</b>                      Steel cold rolled sheets epoxy powder coated 40-60 µ in 200°C 10 steps anti-rust process chemical, corrosion and chip resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinge, adjustable shelving, recessed/integrated handles for safety and heavy duty caster wheel. Customize in color.</p> <p>At 1800mmL side:                      -2 units mobile cabinet single swing door                      -1 unit sink base cabinet  <b>Laboratory sink (for side table):</b>                      Dimension 480mmx380mmWx285mmH/SS316 gauge 1mm industrial grade, seamless with hairline finished.  <b>Laboratory Faucet:</b>                      Connection: G3/8, G1/2, G3/4, standard UNI ISO 228/1.                      Olive-shape nozzle DIN12898.                      Normal regulation headwork or with ceramic closure.                      Max. working pressure 10 bar.                      Optional: Chemical nickel treatment.  <b>Technical features:</b>                      Operating temperature: 30°C to 150°C Chemical resistance:                      Extremely rare alternations. Salt spray test No alternations:                      Kesternichtest: No variation (DIN50018)  <b>Frame and Support:</b>                      2xZ Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot</p> <p><b>Frame and Support:</b>                      2xZ Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot</p> <p><b>Accessories:</b>                      a. 1 Unit SS316 sink bowl seamless and hairline finish complete with traps and piping.                      b. 1 Unit laboratory grade swivel gooseneck faucet with serrated nozzle and complete fittings.                      c. 1 Unit Solid Phenolic pegboard with 36 peg sticks PP                      Pegboard- 710x710, 20mm Solid Phenolic Board chemical resistant with 36 pcs. Peg sticks.                      Peg sticks- 120mm Polypropylene.                      d. 2 units Laboratory Chairs – CH04-1 A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	96,700.00	96,700.00	
8	unit	<p><b>Laboratory Side Table with Reagent Rack</b></p> <p>Dimension: 3400mmLx650mmWx900mmH  <b>Worktop:</b>                      Durcon Solid phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/impact wear resistant, Easy to clean suitable for contact with food.                      With certification on Green guard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF.                      With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties.                      Thickness and Color: 20 mm, Black, beveled edge.</p> <p><b>Cabinets/Drawers:</b>                      Steel cold rolled sheets epoxy powder coated 40-60 µ in 200°C, 10 steps anti - rust process, chemical, corrosion and chip resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinges, adjustable shelving, recessed/ integrated handles for safety and heavy - duty caster wheel. Customize in color.</p> <p>At 3400mmL side:                      -2 units mobile cabinet double swing door  <b>Frame and Support:</b></p> <p><b>Accessories:</b>                      a. 3 units 2 gang Electrical outlet universal 220VAC/15amp splash mounted at 100-130mmH                      Splash board similar to worktop.                      b. Storage rack steel powder coated rack 2 deck with SS304 rail guide.                      c. 2 units Laboratory Chairs – CH04-1 A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p>	1	184,000.00	184,000.00	




Ms. DRTT

Stock/ Property No.	Unit	Particulars	Quantity	Unit Cost	Amount
9	unit	<p><b>Center Assembly Table (Fuel Cell Assembly and Testing Room)</b></p> <p>Dimension: 4400mmLx2200mmWx900mmH</p> <p><b>Worktop:</b>            Durcon Solid phenolic resin electron beam cured and double-sided surface, heat/acid/chemical/stain Resistant with antibacterial properties, at least 10 years guarantee scratch/Impact wear resistant, Easy to clean suitable for contact with food.            With certification on Greenguard, SEFA 3, ISO Certification 9001 &amp; 14001, test for antibacterial resistance and NSF.            With Chemical Resistant Rating of 0 (No Effect) to 1 (excellent) according to SEFA 3 specially on reagent like Acetone, Ethyl ether, benzene hydrofluoric acid, sulfuric acid, nitric acid, etc., and ASTM Test of worktop physical properties.            Thickness and Color: 20 mm, Black, beveled edge.</p> <p><b>Cabinets/Drawers:</b>            Steel cold rolled sheets epoxy powder coated 40-60 µ in 200°C, 10 steps anti-rust process, chemical, corrosion and chip resistant with drawers in full extension heavy duty rail guides, swing door, soft close buffer regressing hinges, adjustable shelving, recessed/ integrated handles for safety and heavy-duty caster wheel. Customize in color.            At 4000mmL side.            -4 units mobile cabinet double swing door            -2 units lateral cabinets with 4 pull out</p> <p><b>Frame and Support:</b>            2x2 Steel Tubular 2.0 mm thick epoxy powder coated frame with heavy duty levelling foot.</p> <p><b>Accessories:</b>            d. 4-units 2 gang Electrical outlet universal 220VAC/15amp retractable.            e. Reagent rack steel powder coated rack 2 deck with ss304 rail guide.            f. 2 units Laboratory Chairs CH04-1A PU (Polyurethane) PU seat and back + 6mm thickness, metal chrome plate with simple, mechanism + 200mm gas lift +, dia450 stainless steel footing + dia640 chrome base + castors.</p> <p><b>Warranty: 1 year on parts and service</b></p>	1	440,000.00	440,000.00
					2,539,800.00
Less: VAT					113,383.92
EWT					22,676.78
<b>TOTAL:</b>					<b>2,403,739.30</b>
END USER:  RONALDO P. PARREÑO JR.					


{Total Amount in Words} : Two Million Four Hundred Three Thousand Seven Hundred Thirty Nine Pesos & 30/100

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent for every day of delay shall be imposed on the undelivered item/s.

Conforme:

  
 Signature over Printed Name of Supplier  
 Ricky C. MANLYTE  
 Date: June 8, 2023

Very truly yours,

  
 DR. ANNABELLE V. BRIONES  
 Signature over Printed Name of Authorized Official  
 Director  
 Designation

Fund Cluster :

THE ESTABLISHMENT OF FUEL CELL R&D AND TESTING FACILITY

ORS/BURS No. FC-202305194

Funds Available :

  
 Signature over Printed Name of Chief Accountant/Head of Accounting Division/Unit Accountant II  
 PATRICIA ASHLEY M. MENDOZA  
 Date: June 7, 2023

Date of the ORS/BURS:

Amount : ₱ 2,539,800.00

