upp/iler	CAS COLO	RAPPLICAT	TION SPECIALIST /	P.O. No. :	GIAE-PO-2024-01-0017 (EBD)		
tdees.			,	Date			
ddress : N :				Mode of Procurement	PB	January 24, 2024	
entlemen:	Places frenish this	Office the following	actions wheat to the terms and conditions contained business	and the second s	/		
			articles subject to the terms and conditions contained herein.				
lace of Deliver ate of Deliver		ONAL METROLOG	DY DIVISION	Delivery Term: 120 CD Payment Term:			
Stock/ Property No.	Unit Particulars			Quantity	Unit Cost	Amount	
	SU	PPLY FABR	RICATION, INSTALLATION, AND DEL	IVERY		7,998,000.00	
	OF ONE (1) UNIT PROTEIN PURIFICATION SYSTEM					.,,	
	ltem	Unit	Descri	ption			
	No.	Qty.					
	1	LOT	Protein Purification System				
			Pand, CVTIVA				
			Brand: CYTIVA Model: AKTA Pure 150L				
			Chromatography System				
			Fraction Collector F9-R				
			UNICORN™ 7 WrkStn pure-BP-e	xn.			
			Workstation for ÄKTA pure™, Äk				
			ReadyToProcess WAVE™ 25				
			UNICORN™ 7 Evaluation Classic				
			Outlet Valve Kit V9H-Os				
			Inlet Valve Kit V9H-IAB				
			Column Valve Kit V9H-C				
			Loop valve kit (V9H-L)				
			pH valve kit (V9H-pH)				
			Superloop™ 50 mL Column Holder				
		PH Probe					
			Benchkote sheets for AKTA pure				
			Specifications:				
			Application supported: Affinity ch				
			chromatography (SEC, also known chromatography, hydrophobic int				
			reversed phase chromatography (				
			F9-R.				
			Buffer selection: upgradeable up				
			Multiple sample valve : Upgradea	able up to 5 inlets and 1	buffer inlet		
			Minimum Buffer Reservoir. 2 Minimum Pressure Monitor Senso	re: 1 Dractura monitor	Dresseure		
			Monitor Range: 0 - 20 Mpa	is. 2 riessure monitor	riessaire		
			Pressure monitor Accuracy: ±0.02N	MPa or ± 2% whicheve	r is greater		
			Minimum Air Sensors: 4 (up to 7)				
			Minimum Injection Valve Ports: 4	(up to 12)			
			System Pump:				
			Flow rate: 0.01 to 150mL/min				
			Pump type: Piston Pump, Met				
			Maximum Operating Pressure: 501 Viscosity: 0.35 to 10.0 cP	par (U to 50 MPa)		COLUMBI	
			Maximum column packing flow ra	te: 300mi/min		I I I I I I I I I I I I I I I I I I I	
			Wetted and Loop materials:	and a second time.	U	1411 0 0 2026	
			Polyetheretherketone (PEEK)		lol	IAN B () ZUZT	







Purchase Order INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE							
oliler:	CAS CO	OR APPLICATION SPECIALIST	P O. No. :		GIAE-PO-2024-01-0017 (EBD)		
Tess .							
			Date		January 24, 2024		
tlemen:			Mode of Procurement	P6			
	Please furnish	his Office the following articles subject to the terms and conditions contained herein					
e of Deliver		CTIONAL METROLOGY DIVISION	Delivery Term : 120 CD Payment Term :				
Stock/ perty No.	Unit	Particulars	Quantity	Unit Cost	Amount		
		Fluorinated Ethylene Propylene (I	ern)				
		Polytetrafluoroethylene (PFTE)	(LF)				
		PolyChloroTriFluoro Ethylene (PC	156)				
		pH Detection:					
		pH monitoring range: 0 to 14					
		pH Accuracy: ±0 1pH unit					
		UV Detection:					
		Wavelength: fixed wavelength (280	nm)				
		Flow Cell path length: Standard option		, illumina	ted		
		cell volume 2 ul, (Options: Optical pa	th length 5 mm)				
		Minimum Lamp Operating Time : > 1	10,000 hours.				
		Tubing i.d.: 1.0mm /o.d. 1/16"					
		Fingertight connectors: 1/16"					
		Tubing connectors:					
		Tubing ID: 2.9mm Tubing o.d.: 3/16", Blue Ferrule					
		Sample Loop:					
		Superloop, 1/16" fittings (AKTA Desig	70) 50ml				
		Loop tubing: I.D. = 0.75mm, o d. 1/1					
		Dimension: 335 x 30mm					
		Fraction Collector					
		Volume Capacity: 175 vessels for 3 n	nl .				
		85 vessels for 15n	nl and				
		40 vessels for 50n	nt				
		Fraction volume : 50ml					
		Weight: 15kg					
		Delay Volume: 473 ul					
		Dimension: (WxHxD)					
		Protein Purification System					
		Width: 535mm					
		Height: 630mm Depth: 470mm					
		Fraction Collector:					
		Width: 320mm					
		Height: 250mm					
		Depth: 400mm					
		Workstation:					
		Width: 400-500 mm					
		Height: 500-600 (comply) Depth: 700-800mm (comply)					
		Power Supply: 100 to 240 V, 50 to 6	O Nz teomolyl				
		Enclosure Protection Class: IP 21	o ric (compiy)				
		Operating Temperature range: 3°C t	o 40°C				
	i	Relative Humidity: 20% to 40%, Nor					
		Safety certifications: CE/ETL/UKCA/I					
		Software: AKTA PURE UNICORN 7 W	Jorkstation Software				
	1	Compatible to the Workstation					
	1	Capable of creating user access					
		Capable of modifying protocols	350				
		With free upgrades/update of softw. Workstation: HP ElitedDesk800 G6					
		AND INSTRUCTION THE UNESTREETING OF	resumption				
		Intel® Core™ i5-10500T with Intel® C	JHD Granhies 630 (2.3	GHz has			
		frequency, up to 3.8 GHz with Intel®					
	1						

Intel® Q470 16G8 (2x8G8) DDR4 2666 SODIMM Memory 256G8 M.2 2280 PCIe NVMe Solid State Drive 1 TB 7200 RPM HDD"

Audio: Integrated audio and powered or built-in stereo speakers, headphone/speaker jack, line-in and line-out mic jacks



eder	CAS COLOR APPLICATION SPECIALIST			P.O. No. =	P.O. No. GIAE-PO-2024-01-0017 (EBD)  Date January 24, 2024				
P35				Date					
			Mode of Procurement PE						
tlemen	Please furnis	h this Office the following articles subject to the term	ns and conditions contained herein.						
of Deliver	y 1	IATIONAL METROLOGY DIVISION		Delivery Term . 120 CO					
nt Delivery	-			Payment Term					
erty No.	Unit	Partice	dars	Quantity	Unit Cost	Amount			
	Pov with	work: Integrated, 802.11ac trating System. Windows 1 yer: 220-240 VAC, 60 Hz i Minimum 4 USB-A ports, board, and DVD±RW drive	1 PRO (64 bit)		g				
	See	attached Warranty Certific	ate						
	lea lea lea lea lea Wittend Har and UPS Bra Price Wa See Two call Del Ma atta	usions Standard accessories of - Outlet Valve Kit V9H-Och - Infet Valve Kit V9H-Och - Infet Valve Kit V9H-Och - Infet Valve Kit V9H-Och - Column Valve Kit V9H-E) is the - pH valve kit (V9H-PH) is the - Superloop <sup>18</sup> 50 mE 181 is the Column Holder 2895C, is the - PH Probe 293871 in Calibration/Validation ceuser dopy and softcopy of Manuels and SECURE, Model: UPS-31 es inclusive of : VAT, delivers support, on-site equipmentation attached Warranty Certificate.  Tranty: See attached warrantatached Warranty Certificate in Calibration Certificate in Calibratic Cert	os 29090694 of 29089652 C 29050951 c 29090689 c 29051684 c 111382 c 282 crtificate upon inst dial in English available. back-up. coovA cry, installation IQ, cent demo. User tra inty certificate icate eventive maintenal de of Requirement	allation witness by able upon delivery /OQ, local and after lining and training nice and services with s/Production &					
	END USER:	KIM CHRISTOPHINE, AGANDA		Less: 1	VAT 357,053.57 CWT 71,410.71 TOTAL:	7,998,000.0 478,464.2 7,569,535.7			
-		Seven Million Five Hundred Sixty Nine T	housand Five Hundred Thir	ty Five Pesos & 72/100					
	f failure to n	ANNA LYNN S. BERN Signature over Printed Name of S January 30, 2024	NABE	Very truly yours,	DR. ANNABELLE V. BRI ture over Printed Name of Auth Director Designation (L.	ONES			

RALLA 1/25/24