
Purchase Order

INDUSTRIAL TECHNOLOGY DEVELOPMENT INSTITUTE



Supplier	ALVTE	LYTECHNOLOGIES PHILIPPINES, INC.		GAAE-PO-2025-02-0015 (MSD		
ddress			Date Mode of Procu	February 21, 2025		
Sentlemen				TOTAL THE CHANGE	Management of the second secon	
Plea	ise furnish t	his Office the following articles subject to the terms and conditions	s contained herein:			
lace of Delivery		MSD Building	Delivery Term: 90 calendar days			
ate of Delivery Stock/ Property	Unit	Dadicular	Payment Term	Unit Cost	Amount	
No.	Unit	Particulars	Quantity	Unit Cost	Amount	
	lot	Supply, Delivery, Installation and Commissioning of one (1) lot BET Surface Area and Pore Size Analyzer and Accessories	1			
		Manufacturer: Anton Paar Specifications: Nova 600				
		Analysis Specifications				
		Measurement Principle: Vacuum Volumetric				
		Analysis gases: N ₂ , Ar, CO ₂ , and other non- corrosive gases Analysis stations: 2 Independent P0 station: Yes				
		Relative pressure range (P/P0): 10 ⁻⁴ to 0.999				
		Pressure measurement accuracy: 0.1% (of full scale)* Pressure resolution: Absolute: 1.2 x 10 ⁻⁴ Torr Relative: 1.5 x 10 ⁻⁷ p/p ₀ Lower specific surface area limit: from 0.01 m²/g Lower absolute surface area limit: from 0.5 m² Surface area reproducibility: 2%** Pore size range: 0.35 - 500 nm (Diameter) (0.35 - 1.1 nm only with CO ₂) Minimum pore value: 1.2x10 ⁻⁸ cm³ Truzone: Yes Powerprotect: Yes Dosewizard: Yes				
		Vectordose: Yes				
		Analysis dewar: Volume: 2 L Duration: Up to 40 hours Sample preparation: Integrated Degassing Stations: 4				
		Temperature Control: 2 Heating Zones. Ambient	1			
		to 425°C Available Methods: Flow & Vacuum, Programmable Multi-step Heating Profiles Physical Specifications				
		Dimensions (DxWxH): 44 cm x 63 cm x 84 cm				
		Weight: 63 kg				
		Operating Environment:				
		Temperature: 15 to 35°C				
		Humidity: 20 to 80% relative, non-condensing Wetted parts: Stainless steel, Viton elastomers				
		Gas:				
		Ports: 5 (3 Analysis, 1 Helium, 1 Degas/Backfill) Purity: 99.999% (He, N2)				
		Input Pressure: 8 to 10 PSIG				
		Vacuum connection: Rolary Pump Exhaust Port, KF16				
		Vacuum requirements: Ultimate vacuum of 2.3 x 10 ⁻³ Torr				
		Electrical				
		Supply: AC 100~240 V AC, 50 / 60 Hz Consumption: 345 VA (Maximum) Page 1	of 2			







25-0013 GF

	ALVTECHNOLOGIES PHILIPPINES, INC.		GAAE-PO-2025-02-0015 (MSD)		
			Date February 21, 2025 Mode of Procurement : Public Bidding		
e furnish th	is Office the following articles subject to the terms and condition		a alexandre de america de america de la constitución de america de		
-	MSD Building	Delivery Term	90 calendar days		
		Payment Term		Andrew Control of the State of	
Unit		Quantity	Unit Cost	Amount	
	, ,		j		
	The state of the s				
	The state of the s				
	CE certified. Yes				
	Nova 600 Surface Area and Pore Size Analyzer		3,484,195.00	3,484,195.0	
			237,684.00	237,684.0	
	Edwards, 1L				
			10,360.00	10,360.0	
	Surface Area Reference Material, 2005		39,077.00	39,077.0	
	Dewar Storage, 5L		91,717.00	91,717.0	
			23,447.00	23,447.0	
			100 100000 1000	73,920.0	
	UPS 3KVA (Silvertec)		19,600.00	19,600.	
	Warranty: 2 years on parts and services				
	merchantability of niness for a particular purpose				
			440		
			177 070 57	3,980,000.0	
				213,214.2	
		EWI		COLUMN TWO IS NOT THE OWNER, OF THE OWNER, WHEN THE PARTY OF THE PARTY	
END HOE	LUMEN MILO		TOTAL.	3,766,785.7	
Mark Service and American Street, St. Co.		d Fighty Five Pesos a	nd 72/100 only		
١	Unit END USEF lords):	Additional specifications Display: 10-inch Touchscreen PC connection: Ethernet Kaomi for Nova Software: Instrument Control: Up to 4 Instruments 6 Languages: English, French, German, Japanese, Chinese, Spanish Kaomi for Nova 21 CFR Part 11 Software: Features: User management, audit trail, customizable reporting, and electronic signature to enhance data integrity for use in the pharmaceutical industry Pharma Qualification Package: Yes Pre-loaded analysis profiles: 20+ (ASTM, USP, DIN, ISO) ROHS 3 compliant: Yes CE certified: Yes Nova 600 Surface Area and Pore Size Analyzer Vacuum Pump, 200-240V with Vacuump Pump Oil, Edwards, 1L Input Line, 5 Feet, Stainless Steel Male Surface Area Reference Material, 2005 Dewar Storage, 5L Sample Holders Set (9mm Set) - Type B Short Cell, 9 mm LG Bulb, Dimple - Sample Cell Adaptor 9 mm - Cell - Seal 9mm, Buna - Non-Elutriating Plug, 9 mm Desktop Computer with Monitor (ACER) UPS 3KVA (Silvertec) Warranty: 2 years on parts and services Others: we do not provide any warranty of merchantability or fitness for a particular purpose	Unit Particulars Additional specifications Display: 10-inch Touchscreen PC connection: Ethernet Kaomi for Nova Software: Instrument Control: Up to 4 Instruments 6 Languages: English, French, German, Japanese, Chinese, Spanish Kaomi for Nova 21 CFR Part 11 Software: Features: User management, audit trail, customizable reporting, and electronic signature to enhance data integrity for use in the pharmaceutical industry Pharma Qualification Package: Yes Pre-loaded analysis profiles: 20+ (ASTM, USP, DIN, ISO) ROHS 3 compliant: Yes CE certified: Yes Nova 600 Surface Area and Pore Size Analyzer Vacuum Pump, 200-240V with Vacuump Pump Oil, Edwards, 1L Input Line, 5 Feet, Stainless Steel Male Surface Area Reference Material, 2005 Dewar Storage, 5L Sample Holders Set (9mm Set) - Type B Short Cell, 9 mm LG Bulb, Dimple - Sample Cell Adaptor 9 mm - Cell - Seal 9mm, Buna - Non-Elutriating Plug, 9 mm Desktop Computer with Monitor (ACER) UPS 3KVA (Silvertec) Warranty: 2 years on parts and services Others: we do not provide any warranty of merchantability or fitness for a particular purpose	Unit Particulars Quantity Unit Cost Additional specifications Display: 10-inch Touchscreen PC connection: Ethernet Kaomi for Nova Software: Instrument Control: Up to 4 Instruments 6 Languages: English, French, German, Japanese, Chinese, Spanish Kaomi for Nova 21 CFR Part 11 Software: Features: User management, audit frail, customizable reporting, and electronic signature to enhance data integrity for use in the pharmaceutical industry Pharma Qualification Package: Yes Pre-loaded analysis profiles: 20+ (ASTM, USP, DIN, ISO) ROHS 3 compliant: Yes CE certified: Yes Nova 600 Surface Area and Pore Size Analyzer Vacuum Pump, 200-240V with Vacuump Pump Oil, Edwards, 1L Input Line, 5 Feet, Stainless Steel Male Surface Area Reference Material, 2005 Dewar Storage, 5L Sample Holders Set (9mm Set) - Type B Short Cell, 9 mm LG Bulb, Dimple - Sample Cell Adaptor 9 mm - Cell - Seal 9mm, Buna - Non-Elutriating Plug, 9 mm Desktop Computer with Monitor (ACER) UPS 3KVA (Silvertec) Warranty: 2 years on parts and services Others: we do not provide any warranty of merchantability or fitness for a particular purpose	